Temprotech

Allprotect™ is made of a strong but flexible polyester non-woven with an impermeable adhesive reverse side. It is designed for critical protection applications and may be applied on most surfaces. Because of its strong adhesion it can be applied to and formed around both horizontal and vertical surfaces without the need for adhesive tape but it also removes without residue for repositioning, disposal or reuse if the backing is undamaged and free from dirt.

The material can be cut into strips and applied to protect vulnerable corners and edges, bandage-wrapped or applied as a sleeve to protect pipework or handrails.

Allprotect™ White protects windows from paint, dust and scratches. It is strongly adhesive and can be applied internally or externally and its translucent quality allows for good light transmission to the workspace.

Allprotect™ is ideal for applications requiring a secure non-slip impact protection which is also impermeable to all kinds of liquids, paints and solvents.

	TPT AllProtect White	TPT AllProtect Flex	TPT AllProtect FR
Top Layer	Polyester/Polypropylene Non-woven	Polyester Non-woven	Polyester Non-woven
Backing	Impermeable PE film	Impermeable PE film	Impermeable PE film
Coating	Pressure-sensitive Acrylic Adhesive	Pressure-sensitive Acrylic Adhesive	Pressure-sensitive Acrylic Adhesive
Thickness	>1.0mm	>2.5mm	>2.5mm
Weight	190g/sqm	250g/sqm	350g/sqm
Tensile Strength	>150N/5mm	>6kN/m	>8kN/m
Colour	White	Light Grey	Dark Grey
Print	Identifying or Custom Print	No Print	No Print
Roll Width	1.0m	1.0m	1.0m
Roll Length	50m	25m	25m
Roll Area	50sqm	25sqm	25sqm
Roll Weight	9.5kg	6.25kg	8.75kg
Extras	6 Month UV Resistant	2 Month UV Resistant	2 Month UV Resistant, Anti-static
FR Approvals			EN13501-1 Cs2, d0

info@temprotech.com
www.temprotech.com

SHIPSERV
TRADENET ID: 252356