



The flame retardant LDPE base films offer excellent puncture and tear resistance. The adhesive applied to the reverse-wound TPTCarpetFR means it can be quickly and easily applied to protect carpets against the spillages, dust and dirt associated with foot traffic in busy workspaces. The specialist acrylic adhesive keeps the **IMO** and **Black Ensign** approved carpet protection securely in place on both new and existing wool or synthetic carpets, yet it can easily be removed without risk of leaving behind traces of residue.

A translucent blue version of the film with a clean-peel acrylic adhesive is ideal for the protection of glass, mirrors, tiles, painted metals, profiles and hard surfaces from dust, dirt, scuffs, scratches and paint overspray.



	TPTSurfaceFR	TPTCarpetFR	TPTCarpetFR
Description	LDPE Film	Reverse-wound LDPE Film	Reverse-wound LDPE Film
Thickness	50 micron	80 micron	80 micron
Adhesive Coating	Acrylic	Acrylic	Acrylic
Colour	Translucent Blue	White	White
Print	No Print	Temprotech and FR Cert	Temprotech and FR Cert
Roll Width	1.0m	0.60m	1.0m
Roll Length	100m	200m	200m
Roll Area	100sqm	120sqm	200sqm
Roll Weight	6kg	9kg	15kg
FR Approvals	BS476 Part 5	IMO Approved 1121/2021 2812/ERO MED0555	Black Ensign Approved 1121/2021 1121/WCL MER0555

Disclaimer

Temprotech products are subject to strict quality control and prove their quality under the most demanding conditions. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Temprotech can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether a product is fit for a particular purpose and suitable for the user's method, application and environment. If you are in any doubt, our technical support staff will be glad to support you.

info@temprotech.com
www.temprotech.com