

TECHNICAL DATA **CORREX® BOXES**

IPTData Correx Boxes.pdf │ © 05-24







Brand leading Correx is extruded from flame retardant polypropylene into a wide range of weights, grades and custom sizes of fluted board.

It provides an extremely versatile form of protection offering light through to heavy duty compression and impact resistance for floors, walls, doors and horizontal surfaces. Correx is light, clean, easy to work with and can be re-used, giving a cost effective alternative to traditional materials.

Custom-designed die-cut protection boxes manufactured from Correx board provide quick and efficient protection for high volume items and superior protection for high value equipment.

A selection of die-cut panels and fixings create a Modular Protection System that offers substantial custom-fit protection for furniture and equipment of all sizes.



















	Capability	TPT3270BS	TPT3350BS	TPT38700BS
Description	Correx® FR	Correx® FR	Correx® FR	Correx® FR
Thickness	2.0-3.5mm	2.1mm	2.6mm	3.5mm
Density	250g-700g/sqm	270g/sqm	350g/sqm	700g/sqm
Colour	White/Black	White	White	White
Print	Custom Print	Temprotech + FR Cert	Temprotech + FR Cert	Temprotech + FR Cert
FR Approvals	LPS1207 Cert. 227a/02	LPS1207 Cert. 227a/02	LPS1207 Cert. 227a/02	LPS1207 Cert. 227a/02
	NFPA 701-2023	NFPA 701-2023	NFPA 701-2023	NFPA 701-2023

Discalmer
Temprotech products are subject to strict quality control and prove their quality under the most demanding conditions. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Temprotech can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether a product is fit for a particular purpose and suitable for the user's method, application and environment. If you are in any doubt, our technical support staff will be glad to support you.

