


## TECHNICAL DATA RUBBER MATTING







Technically advanced rubber-based matting is suitable for most external deck protection applications.

Durable ribbed rubber matting provides a good anti-slip deck protection while interlocking rubber tiles can be used to create excellent heavy duty deck protection. One version has superior drainage capabilities and another offers heavy-duty shock absorption for use in creating Drop Zones for containers and equipment on deck.

Bevelled edging strips are available for the perimeter of areas created with dovetail edge tiles to reduce the trip hazard and allow easy access for lifts and trolleys etc

















	TPT3RM	TPT6RM	TPT9RM	TPT17RMDT	TPT17RMDT-MINI
Description	Ribbed Rubber Matting with Cloth Texture Reverse		Dovetail Edged Mats	Dovetail Edged Mats	
Thickness	3.0mm	6.0mm	9.0mm	17.0mm	17.0mm
Colour	Black	Black	Black	Black	Black
Identification	None	None	None	None	None
Hardness (Shore A)	65	65	65	70	70
Abrasion Resistance	480mm <sup>3</sup>	480mm <sup>3</sup>	480mm <sup>3</sup>	400mm <sup>3</sup>	400mm <sup>3</sup>
Width	1.0m	1.0m	1.0m	1.2m	0.5m
Length	10m	10m	10m	1.8m	0.5m
Area	100sqm	100sqm	100sqm	2.16sqm	0.25sqm
Weight	40kg	80kg	120kg	40kg	4kg
Extras	Dovetail Ramped Edges and Corners also available				



Discalmer
Temprotech products are subject to strict quality control and prove their quality under the most demanding conditions. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Temprotech can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether a product is fit for a particular purpose and suitable for the user's method, application and environment. If you are in any doubt, our technical support staff will be glad to support you.

