



Manufactured from a hard white predominantly closed-cell impact foam and a pressure sensitive acrylic adhesive, this specialist tape creates a water, air and dust seal when compressed. It is ideal for cushioning or gap filling and provides a vibration and rattle-free seal between structural steel and panelling systems or the support brackets for pipework, cabling and HVAC trunking.

With a paper release liner to the non-adhesive face, the tape is quick, clean and easy to apply.



TPTAV3594-340WH	
Description	PVC Foam Tape
Thickness	3mm
Adhesive Coating	Pressure-sensitive Acrylic
Colour	White
Print	No Print
Roll Width	40mm
Roll Length	25m
Roll Area	-
Roll Weight	0.50kg
FR Approvals	BS476 Part 6: 1989 + A1: 2009 + C1: 2014 - Fire Propagation BS476 Part 7: 1997 Class 1 - Surface Spread of Flame

Disclaimer

Temprotech products are subject to strict quality control and prove their quality under the most demanding conditions. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Temprotech can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether a product is fit for a particular purpose and suitable for the user's method, application and environment. If you are in any doubt, our technical support staff will be glad to support you.